

MOTOTRBO™ SL2600

INSTANT COMMUNICATION,
PROFESSIONAL STYLE



GENERAL SPECIFICATIONS

Model Number	SL2600	
Band	VHF	UHF
Frequency	136-174 MHz	403-480 MHz
High Power Output ¹ (Digital)	3 W	
High Power Output (Analogue)	2 W	
Low Power Output	0.5, 1W	
Channel Spacing	12.5, 25kHz	
Channel Capacity	256	
Dimensions (H x W x D), Radio + Standard Battery	125.7 x 55.0 x 22.7 mm	
Weight, Radio + Standard Battery	190g	
Digital / Analogue Battery Life ² (Li-Ion (2300mAh) Battery)	13.5 / 11 hrs	
Power Supply (Nominal)	3.7 V	

TRANSMITTER SPECIFICATIONS

4FSK Digital Modulation	12.5 kHz Data: 7K60F1D and 7K60FXD
	12.5 kHz Voice: 7K60F1E and 7K60FXE
	Combination of 12.5 kHz Voice and Data: 7K60F1W
Digital Protocol	ETSI TS 102 361-1, -2, -3
Conducted/Radiated Emissions (TIA603D)	-36 dBm < 1GHz, -30 dBm > 1GHz
Adjacent Channel Power	60dB (12.5 kHz channel), 70dB (25 kHz channel)
Frequency Stability	± 1.5 ppm

ADDITIONAL FEATURES

- Transmit Interrupt
- Unified Call List
- Enhanced Privacy
- Fixed Privacy Key Decryption
- Ignore Clear Signal
- Bluetooth Audio
- Bluetooth Data
- Indoor Location
- Emergency Search Tone
- Covert Mode
- Intelligent Audio
- Mute Mode
- Noise Suppressor
- Notification List
- Radio Service Menu
- Quick Text Messaging
- User-Selectable Audio Profiles

RECEIVER SPECIFICATIONS

Analogue Sensitivity (12dB SINAD)	0.3 uV, 0.22uV (typical)
Digital Sensitivity (5% BER)	0.25 uV, 0.19uV (typical)
Intermodulation (TIA603D)	70 dB
Adjacent Channel Selectivity, (TIA603A)-1-tone	60 dB (12.5 kHz channel), 70 dB (25 kHz channel)
Adjacent Channel Selectivity, (TIA603D)-2-tone	45 dB (12.5 kHz channel), 70 dB (25 kHz channel)
Spurious Rejection (TIA603D)	70 dB



AUDIO SPECIFICATIONS	
Digital Vocoder Type	AMBE+2™
Audio Response	TIA603D
Rated Audio	0.5 W
Audio Distortion at Rated Audio	5% (3% typical)
Hum and Noise	-40 dB (12.5 kHz channel) -45 dB (25 kHz channel)
Conducted Spurious Emissions (TIA603D)	-57 dBm

BLUETOOTH SPECIFICATIONS	
Version	4
Range	Class 2, 33 ft (10 m)
Supported Profiles	Bluetooth Headset Profile (HSP), Serial Port Profile (SPP), Motorola fast push-to-talk.
Simultaneous Connections	1 x audio accessory and 1 x data device
Permanent Discoverable Mode	Optional

ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature ³	-30 C to +60 C (-22 F to 140 F)
Storage Temperature	-40 C to +85 C (-40 F to 185 F)
Electrostatic Discharge	IEC 61000-4-2 Level 3
Dust and Water Intrusion	IEC 60529 - IP54
Packaging Test	MIL-STD 810D and E

WiFi SPECIFICATIONS	
Standards Supported	IEEE 802.11b, 802.11g, 802.11n
Security Protocol Supported	WPA, WPA-2, WEP
Maximum Number of SSIDs	128

MILITARY STANDARDS										
	810C		810D		810E		810F		810G	
Applicable MIL-STD	Methods	Procedures	Methods	Procedures	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.5	I/A1, II/A1
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
Temperature Shock	503.1	I	503.2	A1/C3	503.3	A1/C3	503.4	I	503.5	I-C
Solar Radiation	505.1	II	505.2	I/Hot-Dry	505.3	I/Hot-Dry	505.4	I/Hot-Dry	505.5	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
Humidity	507.1	II	507.2	II/Hot-Humid	507.3	II/Hot-Humid	507.4	-	507.5	II - Aggravated
Salt fog	509.1	I	509.2	I	509.3	I	509.4	-	509.5	-
Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I
Sand	-	-	510.2	II	510.3	II	510.4	II	510.5	II
Vibration	514.2	VIII/CatF/ CurveW, XI	514.3	I/Cat10, II/Cat3	514.4	I/Cat10, II/Cat3	514.5	I/Cat24, II/Cat5	514.6	I/Cat24, II/Cat5
Shock	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.6	I, IV, V, VI

1: Radio frequency > 470MHz only 2W for Digital.

2: Typical battery life, 5/5/90 profile at maximum transmitter power with Bluetooth and Wi-Fi disabled. Actual observed runtimes may vary.

3: Radio only. Operating temperature specification for a Li-Ion battery is -10 C to +60 C.

For more information, please visit us on the web at: motorolasolutions.com/MOTOTRBO

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2023 Motorola Solutions, Inc. All rights reserved.

FELLECS TECH

FELLECS-TECH Handelsgesellschaft mbH
Moorfleeter Straße 43
Hamburg, Hamburg 22113
www.fellecs-tech.eu
info@fellecs-tech.eu