

ICOM

MARINE RADIOS

for Leisure



TABLE OF CONTENTS

MARINE RADIOS for Leisure

- 03 VHF Marine Handheld Transceivers
- 07 VHF Marine Fixed Mount Transceivers
- 12 MF/HF Marine Transceiver
- 13 AIS Transponders

MARINE RADIOS for Commercial Use

- 17 GMDSS Transceivers
- 19 Marine Radar
- 20 VHF Marine Hybrid Transceivers
- 21 Wi-Fi Transceiver
- 22 Satellite PTT Transceiver



VHF & AIS

VHF Marine

A VHF marine transceiver is a two-way radio communication system designed to communicate with other vessels and coast stations. Also, making distress calls in case of emergency by simplified operation.

AIS Receiver

AIS (Automatic Identification System) is a system designed to help avoid collisions between vessels and serve as a navigation aid. The AIS receiver function on VHF marine radios receives various real-time vessel information, such as the position and heading of nearby AIS-equipped vessels, and displays them on the screen.

Key Features Highlight



Float'n Flash™

The radio will float, flash, and sound an alarm when dropped in water.



AquaQuake™

When the water enters the speaker grill, a low-vibration sound is emitted to remove the water from the grill.



Instant Channel 16 button

Quick access to Channel 16, the international distress and safety channel that boats must monitor even when you are operating on another channel.



Optional speaker-microphone

Optional speaker-microphone provides commercial grade convenience while mounting the radio on the waist.



Distress button & DSC

In case of an emergency, pressing the Distress button will transmit a distress signal and the vessel's position information to other radios in the area.



MOB (Man Overboard) function

Records the location of a person who has fallen overboard. Pressing the distress button while Float'n Flash™ is working will transmit the MOB distress signal.



Functions	IC-M94DE	IC-M73EURO PLUS / IC-M73EURO	IC-M37E	IC-M25EURO EVO
Float'n Flash™	●		●	●
AquaQuake™	●	●	●	●
Distress button & DSC	● (Class H)			
MOB (Man Overboard)	●			
Instant Channel 16 button	●	●	●	●
Optional speaker-microphone	●	●	●	●
AIS receiver				
Receives and displays real-time AIS information from other vessels	●			
Simplified Navigation				
Guides you to a specified waypoint or an AIS target	●			
Integrated GPS (GNSS) receiver				
Determines your vessel's course, speed, and position	●			
CPA/TCPA alarm				
Notifies when the AIS target has entered a set CPA (Closest Point of Approach) or TCPA (Time to CPA)	●			
ATIS channels	● ¹	● ¹	● ¹	● ¹
LCD/key backlight	●	●	●	●
Dualwatch and Tri-watch	●	●	●	●
Checks channel 16 periodically while operating on another channel				
Active Noise Cancelling	●	●		
Reduces background noise by up to 90% for both RX and TX		(IC-M73EURO PLUS)		

Specifications				
Dimensions ² (WxHxD: mm)		60.9 x 145.8 x 43.8	52.5 x 125 x 30	59.7 x 140.5 x 38.7
Weight ³		357 g	320 g	293 g
Audio output power (10% distortion)	Internal speaker	1500 mW typical	700 mW typical	700 mW typical
	External speaker	350 mW typical	200 mW	200 mW typical
RF output power		6 W or 1 W	6 W, 3 W or 1 W 1 W or 0.5 W ⁵	6 W or 1 W
Operating time ⁴		10 hours	17 hours / 20 hours	12 hours
Submersible protection		IPX7	IPX8	IP57
IPX7				

Measurements made in accordance with EN 302-885 for IC-M94DE, EN 301-178 for IC-M73EURO, IC-M37E and IC-M25EURO EVO.

¹ Depending on the transceiver version. ² Projections not included. ³ Approximate. Includes the supplied battery pack, antenna, and belt clip. ⁴ Approximate. Typical operation, Tx : Rx : Stand-by=5 : 5 : 90 with supplied batteries.



VHF Marine Transceiver with DSC & AIS Receiver

IC-M94DE

AIS Traffic Information, Now in Your Hand

- Built-in AIS receiver
- Class H DSC and Distress button
- Simplified Navigation function and MOB
- Float'n Flash™
- 6 W RF output power
- 10 hours of long operating time
- 1500 mW powerful audio output



VHF Marine Transceivers

IC-M73EURO PLUS

IC-M73EURO

Slim, Stylish, Powerful VHF with Professional Features

- IPX8 Advanced Waterproofing
- 6 W RF output power
- 17 hours of operating time
- 700 mW audio output
- Active Noise Cancelling technology*
- Bass Boost function* provides a rich bass sound
- Last call voice recording*

*Available in IC-M73EURO PLUS version only.



VHF Marine Transceiver

IC-M37E

Buoyant 6 Watt VHF with Up to 12 Hours of Operation

- Float'n Flash™
- Large keys and easy-to-grip design
- 6 W RF output power
- 12 hours of operating time
- 700 mW audio output
- Channel history function stores the last five channels



VHF Marine Transceiver

IC-M25EURO EVO

Buoyant VHF with Eco Mode and 14 Hours of Operation

- USB Type-C™ charging port
- Float'n Flash™
- Large keys and easy-to-grip design
- 5 W RF output power
- 14 Hours Operation in power saving Eco mode
- 700 mW audio output



Marine Blue



Key Features Highlight



NMEA connectivity

NMEA 2000™ and NMEA 0183-HS provide data integration with other marine equipment such as an MFD (Multi-Function Display). The radio can transmit GPS (GNSS) position, DSC call, and radio channel.



Simplified Navigation function

Guide you to a specified waypoint or an AIS target. You can assign up to 100 destinations as waypoints.



Distress button & DSC

In case of an emergency, pressing the Distress button will transmit a distress signal and the vessel's position information to other radios in the area.



MOB (Man Overboard) function

Records a GPS position as a MOB waypoint when a person has fallen overboard and needs to be rescued.



Instant Channel 16 button

Quick access to Channel 16, the international distress and safety channel that boats must monitor even when you are operating on another channel.



CommandMic™ station

The radio can be remotely controlled with the optional CommandMic™. Scalability of up to 60.3 ft (18.3 m) maximizes the flexibility to operate anywhere on your boat.



Functions		IC-M605EURO	IC-M510E EVO	IC-M510BB	IC-M410BB	IC-M430E	IC-M423GE	IC-M330GE
NMEA interface	NMEA 2000™	●	●	●	●	●		
	NMEA 0183™	● [HS]	● [HS]	● [HS]	● [HS]	● [HS]	●	●
Simplified Navigation			●					
Distress button & DSC	● [Class D]	● [Class D]	● [Class D]	● [Class D]	● [Class D]	● [Class D]	● [Class D]	● [Class D]
MOB (Man Overboard)		●	●	●				
Instant Channel 16 button	●	●	●	●	●	●	●	●
CommandMic™ station	● [3 stations]	●	● [3 stations]	● [2 stations]	●	●	●	
AquaQuake™ When water enters into the speaker grill, an emitted buzzing sound sheds water from the speaker.	●	●	●	●	●	●	●	●
AIS receiver Receives and displays real-time AIS information from other vessels	● ¹	● ¹	●					
Integrated GPS (GNSS) receiver Determines your vessel's course, speed, and position	●	●	● ²	● ²	●	●	●	●
CPA/TCPA alarm Notifies when the AIS target has entered a set CPA (Closest Point of Approach) or TCPA (Time to CPA)		●	●	●				
ATIS channels	●	●	●	●	●	●	●	●
LCD/key backlight	●	●	●	●	●	●	●	●
Dualwatch and Tri-watch Checks channel 16 periodically while operating on another channel	●	●	●	●	●	●	●	●
Active Noise Cancelling Reduces background noise by up to 90% for both RX and TX	●	●	●	●	●	●	●	
Hailer and Foghorn Talk & listen (2-Way) or listen (1-Way) through the optional SP-37 speaker horn. Foghorn function is also available.	● [2-Way]	● [2-Way]	● [1-Way]	● [1-Way]	● [1-Way]	● [1-Way]		

Specifications

Power supply requirement ³		13.8 V DC	13.8 V DC	12.0 V DC	12.0 V DC	12.0 V DC	13.8 V DC	13.8 V DC
Dimensions ⁴ (W×H×D: mm)		274 × 114 × 121.5	175 × 110 × 53	216 × 79 × 113	216 × 79 × 113	—	180 × 82 × 119.9	156.5 × 66.5 × 88.2
Weight (approximate)		1.51 kg	750 g	RF Unit: 890 g HM-195: 400 g	RF Unit: 870 g HM-195: 400 g	—	1.2 kg	730 g
Audio output power (10% distortion, 4 Ω load)	Internal speaker	—	—	2W [HM-195]	2W [HM-195]	—	—	2 W
	External speaker	15 W	15 W	13 W	13 W	—	10 W typical	4.5 W
RF output power		25 W or 1 W	25 W or 1 W	25 W or 1 W	25 W or 1 W	25 W or 1 W	25 W or 1 W	25 W or 1 W
Submersible protection		IPX8	IP68	IPX7	IPX7	IPX7	IPX7	IPX7

Measurements made in accordance with EN 301 025 for IC-M605EURO, IC-M510E EVO, IC-M430E, IC-M423GE, IC-M510BB, IC-M410BB and IC-M330GE.

¹ Only for the AIS version. ² External GNSS antenna comes with the EUR versions. ³ 10.8 – 15.6 V DC. ⁴ Projections not included.

Please note: The IC-M430E has not been approved by the appropriate authorities in each country. This device may not be sold or leased, or be offered for sale or lease, until approval has been obtained.

VHF Marine Transceiver

IC-M605EURO



VHF Marine Transceiver

IC-M510E EVO



Premium Class D DSC VHF Radio with System Flexibility

- Remote control with up to three Command Head™/CommandMic™
- Integrated AIS receiver and AIS plotter
- NMEA 2000™ and NMEA 0183-HS connectivity
- 4.3-inch colour TFT LCD with wide viewing angle
- Class leading receiver performance (Selectivity and IMD: more than 75 dB)
- 15 W loud audio and 30 W two-way Hailer
- Two minutes last call voice recording



Integrated Class-D DSC VHF Marine Radio with Smartphone App Control

- Remote control & intercom through up to 3 smart devices
- Stylish, sleek design that won iF DESIGN AWARD 2022
- Integrated AIS receiver and AIS plotter*1
- NMEA 2000™ and NMEA 0183-HS connectivity
- 3.5 inch colour TFT LCD with wide viewing angle
- Class leading 15 W audio output
- 25 W two-way Hailer and Fog horn



Remote Control Software
RS-M500

*1 AIS receiver is not included depending on the transceiver version.
Please ask your dealers for details.



VHF Marine Transceiver

IC-M510BB***Up to Three CommandMic™ Capable, Black Box Transceiver***

- Full remote control and intercom (up to three CommandMic™)
- Distress button on the back of the CommandMic™
- Integrated AIS receiver
- NMEA 2000™ and NMEA 0183-HS connectivity
- Built-in GPS (GNSS) receiver (GNSS antenna supplied)
- Internal 13 W Hailer and Foghorn
- Active Noise Cancelling technology
- DSC remote interface to control from other device or PC (EN 300 338-8 compatible)



The IC-M510BB comes supplied with one CommandMic™, HM-195GB.

VHF Marine Transceiver

IC-M410BB***Class D DSC Black Box Transceiver
Up to Two CommandMic™ Capable***

- Full remote control and intercom (up to two CommandMic™)
- Distress button on the back of the CommandMic™
- NMEA 2000™ and NMEA 0183-HS connectivity
- Built-in GPS (GNSS) receiver (GNSS antenna supplied)
- Internal 13 W Hailer and Foghorn
- Active Noise Cancelling technology



The IC-M410BB comes supplied with one CommandMic™, HM-195GB.

NEW

VHF Marine Transceiver

IC-M430E



VHF Marine Transceiver

IC-M423GE



VHF Marine Transceiver

IC-M330GE



Stylish and Compact Communication with Essential Features

- New flush mount method with the same cutout size as the IC-M423GE*
- Slimmer body and sleek design
- NMEA 2000™ and NMEA 0183-HS connectivity
- Colour TFT LCD with wide viewing angle
- Three display modes (Day mode, Dark mode, and Night mode)
- Built-in Class D DSC
- Built-in GPS (GNSS) receiver (built-in GPS antenna)
- Detachable hand microphone can be connected to either the front or rear panel
- Optional HM-195GB/B CommandMic™

Activates soon



* Front panel width differs from the IC-M423GE.

Easy to Hear! Class D DSC Transceiver

- Built-in Class D DSC
- Built-in GPS (GNSS) receiver (GNSS antenna supplied)
- 10 W audio output
- Internal 10 W Hailer and Foghorn
- Active Noise Cancelling technology
- RX speaker function
- Optional HM-195GB/B CommandMic™



High Performance and Compact Body

- Ultra compact body (W156.5 x H66.5 x D88.2 mm)
- Built-in Class D DSC
- Easy-to-read full dot-matrix display
- Built-in GPS (GNSS) receiver* (GNSS antenna supplied)
- Uncompromised receiver performance
- Dynamic clear audio from bass to treble

* IC-M330E (without GNSS receiver) also available depending on the country.



Communication Beyond the Horizon

Marine MF/HF SSB radio is a long-range communication system used on ships for reliable communication over long distances, beyond the reach of VHF radios.

These radios are crucial for maintaining contact with other vessels and shore stations.

Benefits

The key benefits are global communication coverage, enhancing maritime safety. They are essential for emergency and routine communications in the open waters.



MF/HF Marine Transceiver

IC-M804



Long Range Class E DSC MF/HF SSB Radio

- ITU Class E DSC and Distress button
- Dedicated DSC watch-keeping receiver
- 4.3-inch colour TFT LCD with wide viewing angle
- Intuitive user interface
- NMEA 2000™ and NMEA 0183-HS connectivity
- Integrated GPS (GNSS) receiver, and supplied GNSS antenna with 5 m cable
- Two minutes last call voice recording
- Matching design with the IC-M605EURO VHF Marine transceiver



Product photo includes optional AT-141 Antenna Tuner.



Safer Navigation with Real-Time Vessel Information

An AIS transponder is an automatic broadcasting system of real-time vessel information, including identity, position, speed, and course. It helps you to monitor, and be monitored, by AIS-equipped vessels around you.

Benefits

The AIS transponder significantly increases your safety at sea. Other vessels, such as large cargo ships, recognize your vessel position, promoting safer navigation. This exchange of AIS information enhances safe navigation even in low visibility conditions such as fog, rain, or nighttime.

Class B AIS Transponder

MA-510TR**Risk Management and Navigation in One Package**

- 4.3-inch colour TFT LCD with wide viewing angle
- NMEA 2000™ and NMEA 0183-HS connectivity
- Simplified Navigation function
- Silent mode switches OFF the AIS transmitter for privacy
- Multi-language interface (English, French, Indonesian, Spanish and Vietnamese)
- Collision Alarm function
- Anchor Watch function
- USB connectivity to output the received AIS data or GPS data to a PC*¹
- You can pick up AIS targets on the display and send Individual DSC Calls*²



*1 A third party application and a connection cable are required.
 *2 A compatible Icom VHF radio (IC-M605EURO, IC-M510E EVO, IC-M423GE, IC-M510BB, IC-M410BB or IC-M330GE) is required.

NEW

Class B+ AIS Transponder

MA-600TRBB**Broadcast Your Presence, Navigate Confidently**
Black Box AIS Transponder

- Class B+ AIS transponder with SO-TDMA and 5 W output power
- Built-in antenna splitter to share one antenna with a VHF marine radio
- NMEA 2000™ and NMEA 0183-HS connectivity
- Silent mode to pause AIS transmission with the remote ON/OFF switch*¹
- USB Type-C™ port to output the received AIS data or GPS data to a PC*²
- Supplied GNSS antenna supports GPS/GLONASS/Galileo

Activates soon



*1 Silent mode operation requires an external switch (User supplied).
 *2 A third party application and a connection cable are required.

MARINE RADIOS

for Commercial Use





GMDSS Transceivers for SOLAS Ships

The Global Maritime Distress and Safety System (GMDSS) is the International radio safety standard for ships mandated by the International Maritime Organization (IMO).

Merchant ships (SOLAS vessels) are obliged to carry GMDSS communication equipment.



VHF MARINE TRANSCEIVER

GM600



GMDSS VHF Marine Transceiver

- Meets the GMDSS VHF radio requirements for SOLAS ships
- ITU Class A DSC
- Dedicated DSC watch receiver
- Wide viewing angle 4.3-inch colour TFT LCD
- Intuitive user interface
- 10 W audio output power with external speaker
- Certified for European Marine Equipment Directive (MED)



Please note:
PS-310 (#11 or #12) MUST BE USED with GM600
for MED certification compliance.

Optional Accessories for GM600

MUST USE for MED

DC-DC CONVERTER



PS-310 (#11) 24 V input
PS-310 (#12) 12 V input
Provides stable 12.6 V DC output

MED CERTIFIED OPTIONS

HANDSET

HS-98 (#16)
Comes in handy
for listening privacy on board.



HAND MICROPHONE

[IPX7]

HM-214V (#12)
#17 is supplied.



MF/HF Marine Transceiver

GM800**GMDSS MF/HF Transceiver for Long-Distance Communication**

- Meets the GMDSS MF/HF radio requirements for SOLAS ships
- ITU Class A DSC
- Dedicated DSC watch receiver
- Wide viewing angle 4.3-inch colour TFT LCD
- Intuitive user interface
- Certified for European Marine Equipment Directive (MED)



Please note:
HS-98 (#15 is supplied, #17 is an option) and AT-141 (#65) MUST BE USED with GM800 for MED certification compliance.

Optional Accessories for GM800**MUST USE for MED**

AUTOMATIC ANTENNA TUNER



AT-141 (#65)

45 frequency memories for shorter tuning time.

MED CERTIFIED OPTIONS

HANDSET



HS-98 (#17)

#15 is supplied.

HAND MICROPHONE

IPX7

HM-214H (#13)

#15 is supplied.

EXTERNAL SPEAKER



SP-24E (#18)

Input impedance: 4 Ω.
Maximum input power: 7 W.**SHIELDED CONTROL CABLE**

OPC-1465 (#01)

10 m cable.
Use with AT-141.**MOUNTING BRACKET**

MB-108 (#01)

(Photo shows installation example.)



Survival Craft 2-Way Radio

IC-GM1600E**GMDSS Portable for Survival Craft**

- Meets strict environmental requirements for GMDSS
- 2 W output power for long lasting battery
- Primary (non-rechargeable) lithium battery pack, BP-234
- Highly visible yellow-coloured body
- Instant Channel 16 button
- Auto power save



Please note:
BP-234 MUST BE USED with IC-GM1600E to comply with the GMDSS requirements.

Optional Accessories for IC-GM1600E**MUST USE for MED**[For survival craft]
LITHIUM BATTERY PACK

BP-234 (#01)

9.0 V/3300 mAh primary battery pack
for GMDSS survival craft radio.

[For on-board use]

RECHARGEABLE Li-Ion
BATTERY PACK

BP-252 (#01)

7.2 V/1000 mAh [min], 1050 mAh [typ.]
Same as supplied with some versions.

REGULAR CHARGER



BC-173 (#01)

Regularly charges the battery pack,
BP-252 in 10 hours (approx.).

BC-147SE (#59)

Collision Risk Management with Radar Detection

The marine radar system helps vessels detect and track of surrounding objects, shorelines, other vessels, and landmasses, including targets that do not transmit AIS signals.

Benefits

A marine radar enhances safer navigation, especially in fog, rain, or nighttime. When an AIS receiver is connected, you can get additional AIS information including speed and direction of the AIS-equipped vessels. When a VHF marine radio with DSC is connected, received DSC messages including distress are displayed on the radar screen.

**Marine Radar**

MR-1010RII



2 ft Radome Scanner

Marine Radar with 36 NM Range Observation

- Simplified ARPA (Automatic Radar Plotting Aids) function* to track the target and alert e target enters within the CPA and TCPA limits
- 36 NM range, 4 kW radome scanner
- AIS target plotting and overlay AIS functions*
- DSC Information function*
- 10.4-inch colour TFT display
- Intuitive user interface
- Multi-language interface (Arabic, English, French, Italian, Portuguese, Spanish and Turkish)
- True Trail function*
- TLL (Target Latitude Longitude) function*



* External bearing, speed, position, waypoint, variation, AIS and DSC data is [are] required, when you use these functions.

Credits: This product includes "zlib," "libusb," "freetype," "portmap," "ncurses," and "libjpeg" open source software, and is licensed according to the open source software license. This product is based in part on the work of "Eric Young (eay@cryptsoft.com)," and "Independent JPEG Group."

Communication at Sea and on Land

VHF marine is commonly used around the world for maritime safety combined with a land-based LTE or PMR for professional use. It can be used offshore, in ports, rivers, and canals where maritime and business communications are required.

Benefits

The communication range has been expanded by combining two different communication modes in one radio. It is now possible with a single unit, instead of having to carry two transceivers each.



Hybrid IP Transceiver (LTE + VHF Marine)

IP-M60

VHF Marine & LTE Two-In-One Radio

- Nationwide coverage*¹ over LTE networks
- Four Operating Modes (Marine/Cellular/Mixed/Relay)
- Simultaneous TalkListen™ in LTE mode
- Emergency call functions with Man Down and Lone Worker functions
- Built-in Bluetooth® capability and VOX function for hands-free operation
- 1500 mW powerful audio output
- IP67 and MIL-STD-810 rugged construction



Talk Listen
Simultaneous



Dual Mode Transceiver (VHF Marine + PMR)

IC-M85E

VHF Marine & Private Mobile Radio

- 100 programmable PMR channels*²
- Automated Emergency Alarm with Man Down, Lone Worker and MOB Alarm functions
- VOX function for hands-free operation
- 700 mW audio output
- IP67 and MIL-STD-810 rugged construction
- 21 hours of operating time*³
- Built-in voice scrambler compatible



*1 Coverage area depends on the LTE network provider. *2 Appropriate license is required. *3 With a supplied battery, BP-294 [TX: RX: Standby=5:5:90.] Please note: Available functions may be subject to local regulations.



Flexible Communication Solutions

The Wi-Fi transceiver system can be tailored to meet various needs, including license-free Wi-Fi transceivers that support simultaneous full-duplex communication over a Wi-Fi network. In addition, the RoIP (Radio over IP) gateway device seamlessly connects different communication systems.

Benefits

The Wi-Fi transceiver provides crews a seamless and reliable communication solution. With features like Simultaneous TalkListen™ and integration with VHF Marine transceivers and public address systems, this advanced system ensures efficient communication.

Wi-Fi Transceiver **IP110H**



Compact Wi-Fi Radio

- License-free communication terminal
- WPA2™, WPA-Enterprise security
- Built-in Bluetooth® capability
- IP67 and MIL-STD-810
- Compact body and lightweight
- 1000 mW audio output
- Motion/Stationary Detection, Man Down and Lone Worker functions



RoIP Gateway

VE-PG4



Radio over IP Network Gateway

- Links land mobile radios, Wi-Fi transceivers, IP phone systems, satellite PTT transceivers, and external devices
- Wi-Fi transceiver controller built-in, capable of controlling up to 50 Wi-Fi transceivers



Dispatcher Software **RC-FS20**




Virtual Radio/PC Dispatch

- Flexible dispatcher switch layout customization
- Hybrid operation: IP radio systems and land mobile radio (IDAS™)
- Web-based OpenStreetMap display shows up to 300 radio units

Activates soon



Communication Links



Realtime Communication Across the Globe

SATELLITE PTT is a transceiver that uses the Iridium® satellite system, offering global coverage, including both poles. The Iridium® satellite network ensures reliable communication in remote or isolated areas, such as at sea, where no cellular or communications infrastructure exists.

Benefits

Satellite PTT radios enable real-time, broadcast communications with low-latency connections and worldwide coverage. With a simple push of the PTT button, you can instantly communicate with all radios in the same talkgroup.



Satellite PTT IC-SAT100

One-to-Many Global Communications

- Emergency key on the top panel for calling programmed users
- IP67 and MIL-STD-810 rugged construction
- Operating temperature range is from -30°C to +60°C
- 1500 mW of powerful audio
- 14.5 hours of long operating time*1
- Built-in Bluetooth® capability*2
- Integrated GPS (GNSS) receiver
- Location Sharing function to share your location with other Talkgroup participants
- AES 256-bit encryption for security
- Short Data Message function

*1 TX : RX : standby = 5 : 5 : 90.

*2 Version without Bluetooth® capability also available. Ask your dealer for details.

Please Note: Subscription contracts are required for using the IC-SAT100. Depending on the country or region, carrying and/or use of the IC-SAT100 may be prohibited.

Case Study

Japan-Palau Goodwill Yacht Race

Satellite PTT transceivers cover 1726 NM with one-to-many global communication

Scan to see
more details





How the World Communicates

Providing advanced communications, and creating a safe and prosperous society, is what Icom is best at.

We are leading people and society into a bright future by connecting the world with the latest in wireless technology.

Icom is "How the World Communicates."

All stated specifications, appearance, display content, and features are subject to change without notice or obligation. Read all instructions enclosed with the transceiver carefully and completely before using the transceiver. Icom and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. IDAS, SIMULTANEOUS TALKLISTEN, FLOAT'N FLASH, COMMANDMIC, COMMAND HEAD and AQUAQUAKE are trademarks of Icom Incorporated. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Icom Incorporated is under license. NMEA logo, NMEA 2000 and NMEA 0183 are trademarks of the National Maritime Electronics Association, Inc. Iridium and the Iridium connected logo are trademarks and registered trademarks of Iridium Satellite LLC. Windows is a trademark of the Microsoft group of companies. USB TYPE-C is a trademark of USB Implementers Forum Inc. Wi-Fi, WPA2, WPA is a trademark of Wi-Fi Alliance. All other trademarks are the properties of their respective holders.

Icom Inc.

1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302

For the latest information, please visit www.icomjapan.com

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom France s.a.s.
www.icom-france.com

Icom Canada
www.icomcanada.com

Icom Spain S.L.
www.icomspain.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Icom Brazil
E-mail: sales@icombrazil.com

Icom (UK) Ltd.
www.icomuk.co.uk

Icom Asia Co., Ltd.
www.icomasia.com