

Seamless Communication Coverage in 4G LTE and Wi-Fi Condition



IP510H

Automatic Switching in LTE and Wi-Fi

The IP510H can be used in LTE networks and Wi-Fi® environments and automatically switches between them. It is possible to transmit information in a timely manner without worrying about dead zones.

Simultaneous TalkListen™

The TalkListen allows people to talk to each other at the same time. This enables natural interaction and supports multiple conversations with many people.

Built-in Bluetooth® Function

Wireless operation with Bluetooth capability helps improve usability and mobility.

Smallest Class Compact Size

The size and weight are approximately 56 (W) x 92.3 (H) x 31.2 (D) mm with BP-314 and 220 g with BP-314 and antenna.

IP67 Dustproof and Waterproof

IP510H can be used safely even outdoors and in rainy weather.

Security Function

Support for WPA3 Enterprise/Personal and Wi-Fi standards: IEEE802.11 a/b/g/n/ac, which can be connected to a network with a high level of security environment.

OTHER FEATURES

- Call Recording and Playback functions
- Bluetooth® PTT supported (SPP only)
- 1000 mW Loud and Clear Audio
- Vibration Alert
- Short Text Message
- Emergency Button
- Man Down Function
- Lone Worker Function
- USB Type-C™ Charging battery can be replaced without turning OFF the power
- Integrated GPS

OPTIONAL ACCESSORIES

SPEAKER MICROPHONES			HEADSET and PTT SWITCH		HEADSETS and PTT SWITCH/PLUG ADAPTER CABLE				
 HM-222HLS High-power speaker	 HM-183LS	 HM-186LS	 HS-102	 OPC-2359 PTT switch	 HS-94 Earhook type headset	 HS-95 Neck-arm type headset	 HS-97 Headset with throat microphone	 OPC-2328 For manual PTT, and VOX operation	 OPC-2006LS For manual PTT, and VOX operation
EARPHONE-MICROPHONES			BATTERY PACKS		CHARGERS				
 HM-153LS	 HM-166LS	 HM-257LS	 BP-314 Li-Ion 1910 mAh (min.) 2010 mAh (typ.) LTE: 18 hours*	 BP-315 Li-Ion 3050 mAh (min.) 3150 mAh (typ.) LTE: 26 hours*	 BC-269 Multi-connectable Desktop charger	 BC-123S AC adapter for single unit. Straight plug	 BC-228 AC adapter for multiple connections	 BC-258 AC adapter supplied	 OPC-2480 USB cable supplied
BLUETOOTH® HEADSET			CARRYING CASE and BELT CLIP						
 VS-3			 SP-29 Earhook Earphone		 LC-204 Carrying case for BP-314				
			 MBB-3 Belt Clip Same as supplied						

SPECIFICATIONS

GENERAL	
Power Supply Voltage	7.4 V
Dimensions	59.7×144.7×34.9 mm (with BP-314 and Antenna) 59.7×92.3×31.2 mm (with BP-314 and without Antenna)
Weight (approx.)	220 g, 7.7oz (with BP-314 and Antenna)
Operating Temperature	-10 °C to +60 °C
Charging Terminal	USB Type-C™
Operating Time	BP-314: LTE 18 hours, Wi-Fi® 36 hours BP-315: LTE 26 hours, Wi-Fi® 58 hours
Charging Time	BP-314: 120 minutes (with BC-258) BP-315: 200 minutes (with BC-258)
AF Output Power (8 Ω at 5% distortion)	1000 mW (Internal speaker) 250 mW (External speaker) 1000 mW (with HM-222HLS)
Bluetooth® Technology	Ver 5.3
GPS	Built-in
LTE	
Network	(USA)LTE: B2, B4, B5, B12, B13, B14, B25, B26, B66, B71 (EXP/AUS) LTE: B1, B3, B7, B8, B20, B28, 3G (UMTS): 1B, 8B
Output power	+23 dBm typical

Supplied accessories	• Antenna • Beltclip (MBB-3) • Strap • Battery (BP-314) • AC adapter (BC-258A)* • USB cable (OPC-2480)
-----------------------------	-----------------------------------------------------------------------------------------------------------

*for USA version only

Icom and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand, and/or other countries. SIMULTANEOUS TALKLISTEN is trademark of Icom Incorporated. The Bluetooth® word mark and logos are registered trademark owned by Bluetooth SIG, Inc. and any use of such marks by Icom Inc. is under license. USB TYPE-C is a trademark of USB Implementers Forum Inc. Wi-Fi is a registered trademark of Wi-Fi Alliance®. All other trademarks are the properties of their respective holders. Bluetooth® connection has not been tested for all Bluetooth® compatible devices with this product. This does not guarantee that all devices will work with this product.

Wi-Fi®	
Wireless Standards	IEEE802.11 a/b/g/n/ac
Frequency	(USA) 2.4GHz(11ch):1/2/3/4/5/6/7/8/9/10/11 ch 5GHz(25ch):36/40/44/48/52/56/60/64/100/104/108/112/116/120/124/128/132/136/140/144/149/153/157/161/165 ch (EXP/AUS) 2.4GHz(13ch):1/2/3/4/5/6/7/8/9/10/11/12/13 ch 5GHz(19ch):36/40/44/48/52/56/60/64/100/104/108/112/116/120/124/128/132/136/140/149/153/157/161/165 ch
Output power	10 mW/MHz
Security	WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES) WPA3-Personal, WPA3-Enterprise
Maximum Communication speed (Theoretical value)	11/54/150/433 Mbps
IP RATING	
Dust & Water	IP67 (Dust-tight and waterproof)

All stated specifications are subject to change without notice or obligation.

Icom Inc.

1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icomjapan.com

Icom America Inc.
www.icomamerica.comIcom (Europe) GmbH
www.icomeurope.comIcom France s.a.s.
www.icom-france.comIcom Canada
www.icomcanada.comIcom Spain S.L.
www.icomspain.comIcom (Australia) Pty. Ltd.
www.icom.net.auIcom Brazil
E-mail: sales@icombrasil.comIcom (UK) Ltd.
www.icomuk.co.ukIcom Asia Co., Ltd.
www.icomasia.com

FELLECS TECH

Ihr Partner für Funktechnik

www.fellecs-tech.com
inbox@fellecs-tech.com